

Zafety Lug Lock®*

Prevent wheel loss by securing your lug nuts to each other.

Zafety Lug Lock® creates resistance between two nuts to minimize their ability to rotate

The potential for wheel loss continues to be a significant safety concern for the transportation industry



www.zafetyluglock.com



ERNEST C. MANNING
INNOVATION
AWARDS

PRIX
D'INNOVATION
ERNEST C. MANNING

Winner of Canada's most prestigious innovation award
2013 Ernest C. Manning Innovation Award

CA Pat. 2,637,356
US Pat. 8708627 B2*
Made in Canada

Details:

- Fast and easy to install/remove – flexible, simply fits over two adjacent nuts
- Lug nuts can be re-torqued without removing the Zafety Lug Lock®
- Laboratory tested in severe ambient temperature & vibration conditions - standard temperature units from **-40°C to +120°C (-40°F to +248°F)** and high temperature units from **-40°C to +150°C (-40°F to +302°F)**
- Field tested at high and low rotation speeds on all types of surfaces
- 2-year Limited Manufacturers Defect Warranty
- Available in orange, red, white, blue, black, green and custom colours
- Design engineered plastic formulated to withstand extreme changes in temperature
- **Standard temperature units** are designed to withstand continuous operating temperatures from -40 degrees Centigrade (-40°F) to +100 degrees Centigrade (+212°F) with transient temperature spikes up to +120 degrees Centigrade (+248°F)
- **High temperature units** are designed to withstand continuous operating temperatures from -40 degrees Centigrade (-40°F) to +160 degrees Centigrade (+320°F) with transient temperature spikes up to +232 degrees Centigrade (+450°F)-(recommended for vehicles that brake frequently e.g. city transit buses, waste collection)
- Sizes available
 - 27, 30, 32, 33 mm & 38 mm nuts on 3 1/2 inch stud centres
 - 27, 30, 32, & 33 mm nuts on 4 1/8 inch stud centres
 - 38, 41 mm nuts on 4 3/8 inch stud centres
 - 22 & 25 mm nuts on 2 1/2 inch stud centres
 - 21 mm nuts on 2 3/4 inch stud centres

Benefits:

- Provides a clear visual check in all weather and light conditions
- Reduces the risk of potential wheel loss (**Protecting the public and avoiding owner or third party personal, vehicle, property & load damage, lost time & costly towing, road call fees & wheel repairs**)
- Inexpensive, reusable and recyclable

Note: The installation of Zafety Lug Lock® does not exclude the need for standard safety & maintenance procedures.

*Zafety Lug Lock® is a Registered Trademark and CA Pat. 2,637,356 & US Pat. 8708627 B2 of Tafcan Consulting Limited

For more information and ordering, please visit our website at www.zafetyluglock.com